

ՆԿԱՐԱԳԻՐ

առաջարկվող ապրանքի ամբողջական

ԷՅԵՄԵՍ ՍՊԸ-ն ՀՀ ԱՆ ՔԿԾ-ԷԱՃԱՊՁԲ-26/29 ծածկագրով կազմակերպված Էլեկտրոնային աճուրդին մասնակցելու շրջանակում
Ներկայացնում է իր կողմից առաջարկվող ապրանքի ամբողջական նկարագիրը

| Չափաբաժնի համար | Առաջարկվող ապրանքի տեխնիկական բնութագիրը |
|-----------------|--|
| 1 | <p>DS-7732NI-M4 320Mbps Bit Rate Input Max(up to 32-ch IP video), 32x2MP decoding capability, 4 SATA Interfaces, 2 HDMI outputs(up to 8K),1 eSATA,alarm I/O: 16/9, 1.5U case,19" DS-A81024S (2 × 10GbE) 4U, Single controller,180 Ch(2Mbps)Record+playback with IPSAN mode, 512 Ch(2Mbps)Record+playback with Direct steaming mode,24 HDD(SATA), Redundant power supply. DS120HKAI-VX1 3.5 inch Enterprise HDD,12TB,7200,3.5",SATA DS-3E2528-HI-24T4F "24 GE RJ45, 4 GE SFP, Smart L2+ Switch L2+, Smart Managed, 24 Gigabit RJ45 ports, 4 Gigabit SFP ports, Up to 512 IPv4 routing numbers, Loop prevention(RSTP/MSTP/PVST+/RPVST+), Routing(RIP/OSPF/Static), Stackable, IGMP, QoS(SP/WRR/SP+WRR), VLAN(VLAN MAPPING/QinQ), SNMP V1/2/3, Traffic Shaping, HPP/SSH/Console management" DS-3T1512HP-SI-8P4F L2, Smart Managed, 8 Gigabit PoE ports, 4 Gigabit SFP ports, 802.3af/at/bt, port 1-4 support Hi-PoE 90w, power budget<300w(based on power supply, power supply unit not included), -40°C to 75°C, HPP Cloud managed, VLAN, STP/RSTP /ERPS, DHCP Snooping, ACL, IP&MAC filter based on port, SNMP V1/V2C, Max. 300 meter PoE transmission, DIN rail, IP40 HDMI 10m 4k resolution DS-2CD3T87G3-LISUY/SL(4mm) "1/1.8"" Progressive Scan CMOS Color: 0.0005 Lux @ (F1.0, AGC ON),0 Lux with light Fixed iris; Fixed focal lens, 2.8 and 4 mm optional Up to 60 m 50 Hz: 25 fps (3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 30 fps (3840 × 2160□3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) 4 streams; H.265+/H.265/H.264+/H.264/MJPEG; BLC,HLC,3D DNR,Defog WDR 130DB Alarm:2/2 Audio:1/1, Power Output,12 VDC, max. 100 mA DC12V&PoE; Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB IP67,IK10"</p> |

DS-2SR8C440I5XG3-LW/SP/R25/14(F0) "● Adopt integrated camera + radar integrated design, realize automatic calibration, easy installation, easy commissioning, easy deployment ● Support radar-video fusion technology, and supports AI dual large models for video and radar ● Support the detection of the target's distance, azimuth, speed information, and support target positioning, trajectory tracking ● Support radar and video to detect the target, capture the target's face, human body or vehicle pictures during the following process and output related information ● Support smart event, panoramic camera to arm the configured area, when the target is detected, the linkage of the detail camera to follow the target and alarm ● Support display panoramic pictures, detailed pictures, radar sector maps, event alarm maps, face, human body and vehicle snapshots and target structured information through IE ● Support radar and video for perimeter intrusion detection of multiple targets at the same time ● Support detection 24/7 in All-weather such as day, night, rain, fog, etc. ● Suitable for perimeter security scenarios such as industrial parks, enterprise parks, mines, power stations, oil refineries, airports and important centers 4MP 40x PTZ With 100° 500m Perimeter Millimeter Wave" HM-TD2638-10/G0/T1Y "VOx UFPA 384x288 pixels, Pixel pitch 12 μm, NETD< 25 mK, 25 fps thermal frame rate, Support contrast adjustment, 17 palettes of color adjustable, smart features, support bi-spectrum image fusion. Thermographic accuracy (Measurement range): ±8°C (-20~150°C) 1/2.7" CMOS sensor, 4MP(2688× 1520), WDR, BLC 3D DNR, ROI Dual-stream, Streaming in H.265/H.264/MJPEG, Up to 20-ch simultaneous live view, Support Micro SD/SDHC/SDXC Card up to 256G, SDK, ISAPI, Power in DC12V or PoE(802.3af), IP67, IK10; Anti-corrosion coating, NEMA 4X" DS-2SE7C432MWG-EB/26(F0) "· Panoramic channel supports image stitching, with 180° horizontal field of view · High quality imaging with 6 MP resolution in panoramic channel and 4 MP resolution in PTZ channel · Secures an expansive area with 32 × optical zoom and 16 × digital zoom · AcuSense technology focuses on human and vehicle targets classification and supports face capture to detect, capture and select faces in motion · Expansive night view with up to 200 m IR distance in PTZ channel and 30 m white light in panoramic channel · Active strobe light and audio alarm to warn intruders off · Smart-linkage between panoramic channel and PTZ channel"

DS-1603ZJ-P "Wall mount Platinum Gray Aluminum Alloy 364.1 mm × 182.0 mm (14.3" × 7.2") 1400 g (3.09 lb.)" DS-D5055U3-1V0S(EU) 55" 4K, HDMI input, USB multimedia play, with speaker, view angle:178°/178°, 300cd/㎡, VESA 200mm*200mm, base bracket included, 7*24h DS-DM4255W Wall-mounted bracket, Dimension 450 mm × 420 mm × 25mm, VESA 400 (H) mm × 400 (V) mm, recommended for larger size monitor (≥40-inch) HikCentral-P-VER/HW1D/64(E2434) E2434×1/16GB DDR5×1/2T 7.2K SATA×2(RAID_1)/1GbE×2/600W(Dual power)/1U/No DVD/win Svr IOT 2019 Std/3 years PSP HikCentral-P-VSS-1Ch "Video Surveillance Expansion package Prerequisite:Video Surveillance Base package Supported 1 camera manageable." HikCentral-P-Radar-1Unit "Radar Unit Expansion package

Prerequisite: Video Surveillance Base package Warranty: none Supported: -Alarm System 1 radar manageable; Additional none." DS-1600KI(B) 10'1" capacitive touchscreen, detachable design of touchscreen and joystick, preview, PTZ and TV wall control, 4-axis joystick DS-UPS06K-R/TJL/IEC 220V single-phase double conversion online UPS, 6KVA/6KW, PF1.0, rack mounted; input and output wiring blocks, including independent IEC output ports; 6KVA/6KW, PF1.0, single phase online double conversion UPS, rack mounted type; DS-UPSB09240A-R/TJ "External battery pack, can be used with 6/10KVA RACK UPS, 240VDC, built-in 20 9Ah lead-acid batteries External battery pack for use with 6/10KVA UPS, with 20PCS of 9Ah built-in battery;" Հերմետիկ սոււիչ 400*300*200 բանալիով DS-XS6842-E/DG "42U, 600*800*2050mm(including casters); Load bearing: 1000kg Front door with single opening glass door, rear door with single opening steel door" HK-SFP-1.25G-20-1550 TX1550nm/1.25G, RX1310nm/1.25G, LC, single mode and single fiber, 20km, 0-70°C, SFP, should work with HK-SFP-1.25G-20-1310 as a pair HK-SFP-1.25G-20-1310 TX1310nm/1.25G, RX1550nm/1.25G, LC, single mode and single fiber, 20km, 0-70°C, SFP, should work with HK-SFP-1.25G-20-1550 as a pair DS-XPEUR08-Y/KYL (PDU) 8-ports PDU, European standard, Switch, 16A 1.5m input power cable Cable 3*6 Մալուխ 3*6 DS-1LN6OUSPE CAT6 U/UTP Outdoor Network Cable (Solid Copper, 0.55mm) Օպտ.մալուխ OptoWire AS-L-12FO(KFRP)-1.5KN Patchcord SC/UPC - LC/UPC 3.0mm 3m G657A2 LSZH simplex Optimus Стяжки 3,6*200мм черные (100шт) "Цвет оболочки : Черный Количество в упаковке: 100 шт. Материал: Нейлон 66 Рабочая нагрузка: 18 кг Размер: Длина 200 мм, ширина 3,6 мм" Տեսիլսցիկի ոսնակ 2Մ Installation 20 Installation 20 other

ПОЛНОЕ ОПИСАНИЕ

предлагаемого товара

ЕЗЕУЕУ УПС в качестве участника в рамках участия в электронном аукционе под кодом ՀՀ ԱԼ ԶԿԾ-ԷԱՃԱՊՁԲ-26/29 ниже представляет полное описание предлагаемого им товара.

| Номер лота | Предлагаемый товар |
|------------|----------------------------|
| | технические характеристики |
| 1 | |