ՆԿԱՐԱԳԻՐ

առաջարկվող ապրանքի ամբողջական

Ամազոն Իմպորտ ՍՊԸ-ն ԷԱՃԱՊՁԲ-2024/8-3-ԵՊԲՀ ծածկագրով կազմակերպված էլեկտրոնային աճուրդին մասնակցելու շրջանակում ներկայացնում է իր կողմից առաջարկվող ապրանքի ամբողջական նկարագիրը

Չափաբաժնի համար	Առաջարկվող ապրանքի		
	ապրանքային նշանը	մակնիշը	տեխնիկական բնութագիրը
21	D-Link	DGS-1024C	Ցանցային կոմուտատոր 24 պորտ Տեխնիկական բնութագիր. 1000Base-T Interface: 24, Auto MDI/MDIX: Yes, Switching Capacity 48Gbps Max. Packet Forwarding Rate 35.712 Mpps, Store & Forwarding Forwading Yes Power Input AC□100 ~ 240 V Packet Buffer Size: 512KBytes, FAN: Fanless, Comply with RoHS 6 Yes Energy Efficiency Ethernet (EEE) Yes, Power Saving By Link Status Yes Power Saving By Cable Length Yes, MAC Address Table Size: 16000 802.3x Flow Control Yes, Head-of-line (HOL) Blocking Prevention Yes Jumbo Frame 9,216 Bytes, Switch intelligence Unmanaged Port count: 1000Base-T Interface x 24,120G CXP Interface 120G CXP Interface Yes, Storage Humidity: 5% ~ 95% RH Acoustic 0 dB, 1000Base-T Interface 24, 120G CXP Interface Yes Auto MDI/MDIX Yes, SW Capacity 48Gbps, Max. Packet FW Rate 35.712 Mpps Store & Forwarding Forwading Yes, Power Saving By Link Status Yes

ПОЛНОЕ ОПИСАНИЕ

предлагаемого товара

Амазон Импорт ООО в качестве участника в рамках участия в электронном аукционе под кодом ԷԱՃԱՊՁԲ-2024/8-3-ԵՊԲՀ ниже представляет полное описание предлагаемого им товара.

Номер лота	Предлагаемый товар		
	товарный знак	марка	технические характеристики
21	D-Link	DGS-1024C	Сетевой коммутатор, порт 24G 1000Base-T Interface: 24, Auto MDI/MDIX: Yes, Switching Capacity 48Gbps Max. Packet Forwarding Rate 35.712 Mpps, Store & Forwarding Forwading Yes Power Input AC□100 ~ 240 V Packet Buffer Size: 512KBytes, FAN: Fanless, Comply with RoHS 6 Yes Energy Efficiency Ethernet (EEE) Yes, Power Saving By Link Status Yes Power Saving By Cable Length Yes, MAC Address Table Size: 16000 802.3x Flow Control Yes, Head-of-line (HOL) Blocking Prevention Yes Jumbo Frame 9,216 Bytes, Switch intelligence Unmanaged Port count: 1000Base-T Interface x 24,120G CXP Interface 120G CXP Interface Yes, Storage Humidity: 5% ~ 95% RH Acoustic 0 dB, 1000Base-T Interface 24, 120G CXP Interface Yes Auto MDI/MDIX Yes, SW Capacity 48Gbps, Max. Packet FW Rate 35.712 Mpps Store & Forwarding Forwading Yes, Power Saving By Link Status Yes որ 24 պորտ