

ՆԿԱՐԱԳԻՐ

առաջարկվող ապրանքի ամբողջական

Shanxi laboratory Equipment CO LTD-ն ԲԿԳԿ-ԷԱՃԱՊՁԲ-26/15 ծածկագրով կազմակերպված Էլեկտրոնային աճուրդին մասնակցելու շրջանակում ներկայացնում է իր կողմից առաջարկվող ապրանքի ամբողջական նկարագիրը

Չափաբաժնի համար	Առաջարկվող ապրանքի				
	Ֆիրմային անվանումը	ապրանքային նշանը	մակնիշը	արտադրողի անվանումը	տեխնիկական բնութագիրը
1	TOB New Energy co LTD	TOB	TOB	TOB New Energy	The intelligent system of the Internet of Things can be installed to realize the motion control and centralized management of the glove box, which is safe and secure. It has intelligent functions such as real-time synchronization of equipment status, equipment data report records, historical data query, active notification of alarm messages, remote commissioning, online fault diagnosis and online repair, online customer service and other intelligent functions. Control system: Siemens PLC Purifier: single column Moisture

						content: <1ppm Oxygen level :<1ppm Product Specification Glove Box Chamber The Chamber Materials 304SS Thickness :3mm External surface 304SS Inside surface Oil film brushed surface Size Optional length:1500 1800 2440 3660 4880mm Optional depth:750 1000 1200mm Height:900mm Front window Tilt windows, transparent tempered safety glass, thickness 8 mm Glove ports Material is POM or aluminum alloy: O-ring seal Gloves Butyl rubber, thickness 0.4mm, diameter7"or8" Filter 0.3 microns, a gas inlet and a gas outlet Shelf Stainless steel, built- in 2 layers adjustable height Lighting LED lights, LED light, installed in the lampshade Connector DN 40 KF,several spare interfaces,Power interface 1pc (220V) PurificationSystem Purification column Function: gas sealed, remove water, remove oxygen Container material: 304 stainless steel Purification materials: copper catalyst: 5kg, molecular sieve: 5 kg Purification capacity: oxygen: 60L,
--	--	--	--	--	--	---

						water: 2Kg Water and oxygen indicators: less than 1ppm Circulatory system Working gas: nitrogen, argon, helium Recycling capacity: integrated fan flow 90m ³ / h, install frequency conversion(Larger fan flow 145m ³ /h, 180m ³ /h available) Regeneration Operation: PLC automatically controls the regeneration process Regeneration gas: working gas mixed with hydrogen gas, (hydrogen 5-10%) Vacuum pump 8m ³ /h□12m ³ /h Rotary vane pump: with oil mist filter, air vibration control Valves Main valve: DN 40 KF, electrically operated angle valve Control valve: electromagnetic integrated valve Transitive cabin Bigger transitive cabin Chamber Size□diameter 360mm, length 600mm(Optional diameter 400mm) Material: 304 stainless steel Surface: inner surface wire drawing process, outer surface painting or mirror surface Accessary Sliding tray Door: double door, anodized aluminum material, thickness 10mm, vertical operation, with lifting mechanism Pressure gauge: Analog display Control Operation: Automatic control
--	--	--	--	--	--	--

				Smaller transitive cabin Chamber Size □diameter150mm□length300mm□Opti onal diameter100mm□ Material: 304 stainless steel Surface: inner surface wire drawing process, outer surface painting or mirror surface Accessary Door: double door Pressure gauge: Analog display Control Operation: Manual operation Control System Descriptions Display system□Siemens PLC Touch Panel Function□Including self-diagnosis, power-off self-starting characteristics, with pressure control and adaptive function Automatic control, cycle control, password protection Pressure control□Control box, transition chamber pressure, cabinet working pressure +/- 15mbar can be set freely, beyond +/- 16mbar system automatic protection Pedal□Control the box pressure Data Memo□Automatic recording the system data Accessary Vacuum Pumps Specification□8m³/h□12m³/h□16m³/h Oxygen analyzer Measurement range□0□1000ppm Humidity (dew point) Instrument Measurement range□0□500ppm
--	--	--	--	---

ПОЛНОЕ ОПИСАНИЕ

предлагаемого товара

Shanxi laboratory Equipment CO LTD в качестве участника в рамках участия в электронном аукционе под кодом РЧРЧ-ЕЦДЦПДР-26/15 ниже представляет полное описание предлагаемого им товара.

Номер лота	Предлагаемый товар				
	фирменное наименование	товарный знак	марка	наименование производителя	технические характеристики
1	TOB New Energy co LTD	TOB	TOB	TOB New Energy	The intelligent system of the Internet of Things can be installed to realize the motion control and centralized management of the glove box, which is safe and secure. It has intelligent functions such as real-time synchronization of equipment status, equipment data report records, historical data query, active notification of alarm messages, remote commissioning, online fault diagnosis and online repair, online customer service and other intelligent functions. Control system: Siemens PLC Purifier: single column Moisture

						content: <1ppm Oxygen level :<1ppm Product Specification Glove Box Chamber The Chamber Materials 304SS Thickness :3mm External surface 304SS Inside surface Oil film brushed surface Size Optional length:1500 1800 2440 3660 4880mm Optional depth:750 1000 1200mm Height:900mm Front window Tilt windows, transparent tempered safety glass, thickness 8 mm Glove ports Material is POM or aluminum alloy: O-ring seal Gloves Butyl rubber, thickness 0.4mm, diameter7"or8" Filter 0.3 microns, a gas inlet and a gas outlet Shelf Stainless steel, built- in 2 layers adjustable height Lighting LED lights, LED light, installed in the lampshade Connector DN 40 KF,several spare interfaces,Power interface 1pc (220V) PurificationSystem Purification column Function: gas sealed, remove water, remove oxygen Container material: 304 stainless steel Purification materials: copper catalyst: 5kg, molecular sieve: 5 kg Purification capacity: oxygen: 60L,
--	--	--	--	--	--	---

water: 2Kg Water and oxygen indicators: less than 1ppm Circulatory system Working gas: nitrogen, argon, helium Recycling capacity: integrated fan flow 90m³ / h, install frequency conversion(Larger fan flow 145m³/h, 180m³/h available) Regeneration Operation: PLC automatically controls the regeneration process Regeneration gas: working gas mixed with hydrogen gas, (hydrogen 5-10%) Vacuum pump 8m³/h□12m³/h Rotary vane pump: with oil mist filter, air vibration control Valves Main valve: DN 40 KF, electrically operated angle valve Control valve: electromagnetic integrated valve Transitive cabin Bigger transitive cabin Chamber Size□diameter 360mm, length 600mm(Optional diameter 400mm) Material: 304 stainless steel Surface: inner surface wire drawing process, outer surface painting or mirror surface Accessary Sliding tray Door: double door, anodized aluminum material, thickness 10mm, vertical operation, with lifting mechanism Pressure gauge: Analog display Control Operation: Automatic control

				Smaller transitive cabin Chamber Size □diameter150mm□length300mm□Opti onal diameter100mm□ Material: 304 stainless steel Surface: inner surface wire drawing process, outer surface painting or mirror surface Accessary Door: double door Pressure gauge: Analog display Control Operation: Manual operation Control System Descriptions Display system□Siemens PLC Touch Panel Function□Including self-diagnosis, power-off self-starting characteristics, with pressure control and adaptive function Automatic control, cycle control, password protection Pressure control□Control box, transition chamber pressure, cabinet working pressure +/- 15mbar can be set freely, beyond +/- 16mbar system automatic protection Pedal□Control the box pressure Data Memo□Automatic recording the system data Accessary Vacuum Pumps Specification□8m³/h□12m³/h□16m³/h Oxygen analyzer Measurement range□0□1000ppm Humidity (dew point) Instrument Measurement range□0□500ppm
--	--	--	--	---

